

Amendments to the Specification

Amendments are made to the specification as shown in the following replacement paragraphs or sections. The changes in comparison to the immediate prior version are shown.

Please amend paragraph [0056] as set forth below:

[0056] In this regard, a subassembly 26 couples the pivot arm 10 to the electronic display 14, and includes a swivel 28 through which a swivel axis 30 passes, a mounting member 32, and an elongate member 34 extending between and connecting together the swivel 28 and the mounting member 32. The elongate member 34 is pivotably mounted to the swivel member 28 for pivoting movement about pivot axis 36. As shown in FIG. 1, the swivel axis 30 and the pivot axis 36 are coplanar. The elongate member 34 also is pivotably mounted to the mounting member 32 for pivoting movement about pivot axis 38. The elongate member 34 is rotatable about the swivel axis 30 and includes two elongate side bars 40. The coupling of the elongate member 34 to the swivel 28 includes a post that extends downwardly from the swivel 28, to which both elongate bars 40 are directly secured by a first clamp bolt assembly and nut. Similarly, both elongate bars 40 are directly secured to a post portion 42 of the of the mounting member 32 by a second clamp bolt assembly and nut. The mounting member 32 is removably attached via screws 44 directly to the electronic display 14 in fixed relation thereto.

Please amend paragraph [0057] as set forth below:

[0057] The pivot arm 10 comprises a pair of parallel elongate members [[40]] joined to form a four-bar-linkage parallelogram, and the pivot arm 10 is pivotable about a pivot axis 46 and another pivot axis 48. The pivot axis 46 passes through the distal end 16 of the pivot arm 10, and the pivot axis 48 passes through the distal end 24 of the pivot arm 10. As will be appreciated by one having ordinary skill in the art, the design of the pivot arm 10 is such that raising or lowering of the electronic display 14 by pivoting movement of the pivot arm 10 about both pivot axes 46,48 permits the swivel axes 22,30 to remain in parallel relation. [0056] In this regard, a subassembly 26 couples the pivot arm 10 to the electronic display 14, and includes a swivel 28 through which a swivel axis 30 passes, a mounting

member 32, and an elongate member 34 extending between and connecting together the swivel 28 and the mounting member 32. The elongate member 34 is pivotably mounted to the swivel member 28 for pivoting movement about pivot axis 36. The elongate member 34 also is pivotably mounted to the mounting member 32 for pivoting movement about pivot axis 38. The elongate member 34 is rotatable about the swivel axis 30 and includes two elongate side bars 40. The coupling of the elongate member 34 to the swivel 28 includes a post that extends downwardly from the swivel 28, to which both elongate bars 40 are directly secured by a first clamp bolt assembly and nut. Similarly, both elongate bars 40 are directly secured to a post portion 42 of the of the mounting member 32 by a second clamp bolt assembly and nut. The mounting member 32 is removably attached via screws 44 directly to the electronic display 14 in fixed relation thereto.

Please amend paragraph **[0068]** as set forth below:

[0068] The send unit **62** is shown in **FIG. 3** as being attached to a wall; however, the send unit **62** may be disposed anywhere so long as the receive units **66,68** are within its transmission range. Alternative locations include being secured to the support to which the track 56**[[50]]** is mounted.